

# MODEL: ID200 MAN-PORTABLE DRILL RIG

## **SPECIFICATIONS**

Engine: Kubota V1505 30HP @ 3000Rpm

Hydraulics: Fixed displacement gear pump, 2 segments, 60 litres and 30 litres @ 210 Bar.

Filtration: In-Tank filter on return Oil

Hydraulic Tank: Capacity 150 litres

Heat Exchanger: Hydraulic Oil Cooler, Water Cooled

**Mast:** Lattice boom construction, Allows 1.8 metres head travel, directly coupled to traverse cylinder. Mast Length 6.5 Metres allows for 6 Metre rod pull.

Pull Back: 2,500Kg @ 210 Bar

Pull Down: 1,000Kg @ 120 Bar

Main Winch: 2,700Kg @ 210 bar bare drum pull, 18 Metres 10mm wire rope

Wire Line Winch: 600Kg @ 210 bar, 250 metres 6mm wire rope.

**Rotation Head:** Oil bath single gear reduction, 3.3:1 speed 610rpm, Torque 335 Nm @ 210 Bar, Head slide to allow 6 Metre rod pull.

**Control Panel:** All hydraulic, electrical and instrumentation are mounted at the control panel.

Head Traverse: Fast feed 0.5 M per sec, slow feed 0-2 M per min.

Foot Clamp: Hydraulic Cylinders open/close, eccentric cam, tungsten insert jaw.

Drilling Capacity: PQ - 50 Metres / HQ - 100 Metres / NQ - 200 Metres.

Approximate Overall Rig Weight: 1,800kg

#### OFFICE ADDRESS



## ID200 Man-Portable Drill Rig



#### OFFICE ADDRESS

Indodrill Group Holdings Pte Ltd 20 Changi South Avenue 2 KWE Building, Singapore 486547

#### TELEPHONE NUMBER (65) 654 393 75



## ID200 Man-Portable Drill Rig





#### OFFICE ADDRESS

Indodrill Group Holdings Pte Ltd 20 Changi South Avenue 2 KWE Building, Singapore 486547

### TELEPHONE NUMBER (65) 654 393 75